

# ストレートシャンクロングドリル (HSS)

一般市場品として、もっとも広い用途で使用されるロングドリルです。  
切屑の排出を考慮し、深穴加工や深い位置の穴明加工に最適です。



(φ2.0以上)

(単位: mm)

直径 Drill Dia.	全 長 Overall Length							
	75 溝長 Flute Length	100 溝長 Flute Length	125 溝長 Flute Length	150 溝長 Flute Length	200 溝長 Flute Length	250 溝長 Flute Length	300 溝長 Flute Length	350 溝長 Flute Length
0.5	10	15		15				
0.6	10	15		20				
0.7	15	20		25				
0.8	15	20		25				
0.9	20	30		35				
1.0	30	40	40	50	50			
1.1	35	40	40	50	50			
1.2	35	40	40	50	50			
1.3	35	40	40	50	50			
1.4	35	40	40	50	50			
1.5	40	40	40	50	50			
1.6	40	50	50	50	50			
1.7	40	50	50	50	50			
1.8	40	50	50	50	50			
1.9	40	50	50	50	50			
2.0		50	65	75	100	120	150	
2.1		50	65	75	100	120	150	
2.2		50	65	75	100	120	150	
2.3		50	65	75	100	120	150	
2.4		50	65	75	100	120	150	
2.5		50	65	75	100	120	150	175
2.6		50	65	75	100	120	150	175
2.7		50	65	75	100	120	150	175
2.8		50	65	75	100	120	150	175
2.9		50	65	75	100	120	150	175
3.0		50	65	75	100	120	150	175
3.1		50	65	75	100	120	150	175
3.2		50	65	75	100	120	150	175
3.3		50	65	75	100	120	150	175
3.4		50	65	75	100	120	150	175
3.5		50	65	75	100	120	150	175
3.6		50	70	75	100	125	150	175
3.7		50	70	75	100	125	150	175
3.8		50	70	75	100	125	150	175
3.9		50	70	75	100	125	150	175
4.0		50	70	75	100	125	150	175
4.1		50	70	75	100	125	150	175
4.2		50	70	75	100	125	150	175
4.3		50	70	75	100	125	150	175
4.4		50	70	75	100	125	150	175
4.5		50	70	75	100	125	150	175
4.6		50	70	90	100	125	150	175

φ2.0未満の寸法は表面処理なし



# ストレートシャンクロングドリル (HSS)



(φ2.0以上)

(単位: mm)

直径 Drill Dia.	全 長 Overall Length							
	75 溝長 Flute Length	100 溝長 Flute Length	125 溝長 Flute Length	150 溝長 Flute Length	200 溝長 Flute Length	250 溝長 Flute Length	300 溝長 Flute Length	350 溝長 Flute Length
4.7		50	70	90	100	125	150	175
4.8		50	70	90	100	125	150	175
4.9		50	70	90	100	125	150	175
5.0		50	70	90	100	125	150	175
5.1			70	90	100	125	150	175
5.2			70	90	100	125	150	175
5.3			70	90	100	125	150	175
5.4			70	90	100	125	150	175
5.5			70	90	100	125	150	175
5.6				90	100	125	150	175
5.7				90	100	125	150	175
5.8				90	100	125	150	175
5.9				90	100	125	150	175
6.0				90	100	125	150	175
6.1				90	100	125	150	175
6.2				90	100	125	150	175
6.3				90	100	125	150	175
6.4				90	100	125	150	175
6.5				90	100	125	150	175
6.6				90	100	125	150	175
6.7				90	100	125	150	175
6.8				90	100	125	150	175
6.9				90	100	125	150	175
7.0				90	100	125	150	175
7.1				90	100	125	150	175
7.2				90	100	125	150	175
7.3				90	100	125	150	175
7.4				90	100	125	150	175
7.5				90	100	125	150	175
7.6				90	125	150	175	200
7.7				90	125	150	175	200
7.8				90	125	150	175	200
7.9				90	125	150	175	200
8.0				90	125	150	175	200
8.1				90	125	150	175	200
8.2				90	125	150	175	200
8.3				90	125	150	175	200
8.4				90	125	150	175	200
8.5				90	125	150	175	200
8.6				90	125	150	175	200
8.7				90	125	150	175	200
8.8				90	125	150	175	200



# ストレートシャンクロングドリル (HSS)



(φ2.0以上)

(単位: mm)

直径 Drill Dia.	全 長 Overall Length							
	75 溝長 Flute Length	100 溝長 Flute Length	125 溝長 Flute Length	150 溝長 Flute Length	200 溝長 Flute Length	250 溝長 Flute Length	300 溝長 Flute Length	350 溝長 Flute Length
8.9				90	125	150	175	200
9.0				90	125	150	175	200
9.1				90	125	150	175	200
9.2				90	125	150	175	200
9.3				90	125	150	175	200
9.4				90	125	150	175	200
9.5				90	125	150	175	200
9.6				90	125	150	175	200
9.7				90	125	150	175	200
9.8				90	125	150	175	200
9.9				90	125	150	175	200
10.0				90	125	150	175	200
10.1					125	150	175	200
10.2					125	150	175	200
10.3					125	150	175	200
10.4					125	150	175	200
10.5					125	150	175	200
10.6					125	150	175	200
10.7					125	150	175	200
10.8					125	150	175	200
10.9					125	150	175	200
11.0					125	150	175	200
11.1					125	150	175	200
11.2					125	150	175	200
11.3					125	150	175	200
11.4					125	150	175	200
11.5					125	150	175	200
11.6					125	150	175	200
11.7					125	150	175	200
11.8					125	150	175	200
11.9					125	150	175	200
12.0					125	150	175	200
12.1					125	150	175	200
12.2					125	150	175	200
12.3					125	150	175	200
12.4					125	150	175	200
12.5					125	150	175	200
12.6					125	150	175	200
12.7					125	150	175	200
12.8					125	150	175	200
12.9					125	150	175	200
13.0					125	150	175	200

